



Philips
LCD monitor

32"

multimedia WXGA

BDL3221V



Control your communications

This robust network-controllable 32" LCD monitor puts you in charge of your message. Manage your costs, deliver a stunning public display performance and adapt to multiple applications with ease.

Optimised for public viewing

- Wide format WXGA 1366 x 768 resolution for sharper display
- Brightness automatically adjusts with ambient conditions

Designed for public areas

- Robust metal bezel and metal back cover
- Security feature prevents unauthorised control

Operational flexibility for different applications

- Monitor is network controllable for remote management
- Enhanced zoom feature supports tiled matrix applications
- VGA loop through enables daisy chaining to multiple monitors
- Portrait mode operability
- Optional TV tuner

Lower total cost of ownership

- Intelligent power management for lower consumption
- No permanent burn-in when static information is displayed

PHILIPS
sense and simplicity

Specifications

Picture/Display

- LCD panel type:** 1366 x 768 pixels, Anti-glare polariser
- Panel Size:** 32"/81.28cm
- Aspect ratio:** 16:9
- Pixel pitch:** 0.170x0.511mm/0.067x0.201"
- Brightness:** 500 cd/m²
- Contrast ratio (typical):** 1000:1
- Display colours:** 16.7 million colours
- Viewing Angle (H / V):** 178 / 178 degree
- Response time (typical):** 8 ms
- Recommended Resolution:** 1360 x 768 @ 60Hz
- Horizontal Scanning Frequency:** 30–63 kHz
- Vertical Scanning Frequency:** 56 – 75 Hz
- Picture enhancement:** 3D Combfilter, De-interlacer, Picture in Picture, Progressive Scan

Supported Display Resolution

Computer formats

Resolution	Refresh rate
640 x 480	60, 75 Hz
720 x 400	70 Hz
800 x 600	60, 75Hz
1024 x 768	60, 75Hz
1280 x 768	60 Hz
1360 x 768	60 Hz

Video formats

Resolution	Refresh rate
480i	60 Hz
480p	60 Hz
576p	50 Hz
576i	50 Hz
720p	50, 60 Hz
1080i	50, 60 Hz

Connectivity

- PC:** 3.5 mm PC audio input x1, DVI-D with HDCP, RS232 D-Sub9, RS232 D-sub9 output, VGA-in D-Sub 15HD, VGA-out D-Sub 15HD
- AV input:** Component (YPbPr) x1, Audio (L/R) for YPbPr x1, Composite (CVBS) x1, Audio (L/R) x1, S-video x1, SCART x1
- AV output:** Composite (CVBS) x1, Audio (L/R) x1
- Audio output:** Stereo Audio (3.5 mm jack) 1x, External loudspeaker connector

Convenience

- Picture in Picture:** 1 tuner PIP, Double window

- Convenience Enhancements:** Automatic Brightness Control, Automatic Overheat Warning, On-screen Display
- OSD Languages:** English, French, German, Italian, Spanish, Simplified Chinese
- Detachable Audio:** 2x10 W RMS Speakers
- Onboard Operating Controls:** Hidden controls
- Other convenience:** Cable management, Carrying handles, Kensington lock
- Plug & Play Compatibility:** sRGB, Windows 98/ME/2000/XP
- Network controllability:** RS232
- VESA Mount:** 200 x 200 mm
- Regulatory Approvals:** C-Tick, CE Mark, FCC-B, UL, CSA, MPRII, TÜV/GS

Power

- Consumption:** typ. 100 W (PC), 130 W (TV)
- Power supply:** Built in, 90-264 VAC, 50/60 Hz
- Sleep Mode:** <2W

Dimensions

- Dimensions (w/o base & speakers) (W x H x D):** 794 x 490 x 130 mm
- Width (with speakers):** 1014 mm
- Set dimensions in inch (W x H x D):** 31.26 x 19.29 x 5.12 inch
- Width (with speakers) (inch):** 39.921 inch
- Weight:** 19.2 kg
- Product weight (lb):** 42.33
- MTBF:** 50,000 hrs
- Temperature (operation):** 0°C to +35°C
- Relative humidity:** 5% - 90%

Accessories

- Included Accessories:** Speakers (L/R), Table top stand (2 feet), DVI-D cable, VGA cable, Remote Control, Battery, AC Power Lead
- Optional accessories:** PAL tuner box BPL4221R1, Ceiling mount BM04111&BM01111, Fixed wall mount BM02111, Flex wall mount BM04111&BM02212
- User Guide on CD-ROM

Miscellaneous

- Warranty:** Europe: 3 years on site, APMEA: 1 year
- Bezel:** metallic anthracite

Product highlights

WXGA 1366 x 768 resolution

The wide format of XGA resolution LCD panel is capable of displaying 1366 x 768 pixels; WXGA allows monitors to be non-interlaced to ensure a better display performance and accurate colour display effect.

Automatic brightness control

The adjustment of display settings to correspond with ambient light without user intervention.

Robust metal bezel

Specially designed for demanding public applications, the metal bezel offers higher durability and protection against vandalism. Anodised paint is used to offer extra protection of the bezel against scratches.

No unauthorised control

The local controls of the display are placed in such a way that they are less visible for immediate access. Furthermore the remote control sensor and the keypad on the display can be disabled via RS232 in order to prevent unauthorised control of the display when placed in a public space.

Network controllability: RS232

Network controllability allows user to control and adjust monitors remotely through RS232 protocol.

Zoom function for tiled matrix

The internal zoom function enables easy implementation of a video wall matrix, without the need for expensive external equipment. Capable of 2x2, 3x3, 4x4 and 5x1 configurations.

Signal loop through

Multiple screen daisy chain effectively distributes control and visual content from a single source to an array of monitors in various locations within a site.

Portrait mounting possible


This display can also be safely and reliably mounted in portrait position.

Optional TV tuner

An optional TV tuner can be ordered separately and installed by the user by simply plugging in the unit in a slot at the back of the monitor. When switching on the monitor the tuner will be recognised.

Intelligent power management

Intelligent power management employs energy-efficient technologies in product design to reduce power consumption and significantly lower the total cost of ownership.



Issue date 2008-05-16

Version: 6.0.17

12 NC: 8639 000 16304
EAN: 87 10895 89669 6

© 2008 Koninklijke Philips Electronics N.V.
All Rights reserved.

Specifications are subject to change without notice.
Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com